



**CARTA DA PARATI
ARTISTICA**

 **CARTA DA PARATI**
ARTISTICA
Emozioni d'autore

Made in Italy
 

Our company

- 4 Our mission
- 6 Our architect ' s advice
 - Digital Rendering
 - Project
 - Manufacturing time
 - Customization

Wall covering Vinyl + non woven fabric

- 9 Description
 - Materials
 - Wall covering cleaning
 - Wall covering paste supplied
- 10 Use of non woven fabric + vinyl
 - Technical features
 - Details
- 11 Warranty
- 13 Inks Quality control
 - Installation

Wall covering Fiberglass

- 15 Description
 - Materials
 - Wall covering cleaning
 - Wall covering paste to use
- 16 Use of fiberglass
 - Technical features
- 17 Warranty
- 19 Inks Quality control
 - Installation
- 20 Resin

■ OUR MISSION

We create **unique pieces**. We do not offer wall covering rolls ready to sell but we create them on request.



- **SIZE**

Each wall covering is created considering height and width provided by client and the pattern is adapted considering the given size.




- **COLOURS**

Clients can personalise the wallpaper colours considering his needs only indicating the colours' names or the Pantone® code.



- **POSITION**

Graphic pattern will be placed considering furnitures which could hide it. Client has to indicate the right position and size of each furniture in order to give the greatest visibility to the wall covering pattern.



- **MIRROR**

If the wall has a door or a window, we can mirror the subject of the wallpaper, placing it on the opposite side, in order to give a good visibility.



■ OUR ARCHITECT' S ADVICE

Our architect can help suggesting which patterns fit better. This is an exclusive service of Carta da Parati Artistica in order to avoid mistakes and to give precise details on the more suitable patterns considering both the residential or commercial setting.

■ DIGITAL RENDERING

Client can view which graphic fits better thanks to a digital rendering set by our graphic division. To obtain this service client has to send a picture of the wall to decor by e-mail or whatsapp.

■ PROJECT

Before confirming the wall covering printing client has to approve a project that our graphic division will send by e-mail.

For a good job it is necessary to provide:

- exact height and width of the wall
- baseboard height
- accurate room measurements: height and width of the all components on the wall (beds, sofas, furnitures, ...)


■ MANUFACTURING TIME

Our philosophy is to create high-level coverings in short and certain time. Our manufacturing system is organised to optimise all production processes.

■ CUSTOMIZATION

Our artists division can create patterns on demand considering the client's needs.





WALL COVERING
Vinyl + non woven fabric



■ Description

The vinyl – non woven fabric wallpaper is a strong wallcover and it is the ideal solution to decor surfaces both in residential and commercial environments.

It can cover walls, ceilings or furnitures like doors or wardrobe doors.

Installation is suggested in standard environmental conditions.

Hang wallpaper with the paste supplied.

■ Materials

The wallpaper is composed of two layers.

Vinyl Front:

- surface is rough to the touch as a pictorial canvas effect
- **washable;**
- the opacity touch gives a perfect output of colours

Non woven fabric:

- easy installation as the paste is applied directly on the wall
- possible removal from the wall with no leftovers.



■ Wall covering Cleaning

- Mix water and neutral soap or use a wallcovering detergents. Never use aggressive liquids as alcohol which could ruin and bleach the colours.
- Clean up softly sponging without scrubbing
- Dry afterwards with a soft and dry clothe

■ Wall covering paste supplied

In the package there is one or more *Metylan Sichozell* wallpapers paste boxes. Follow instructions on how to prepare the wallpaper paste

■ Use of non woven fabric + vinyl



Walls



Ceilings



Wardrobes



Residential



Commercial

■ Technical Features

- Total weight 350 ± 20 g/m²
- Non wover fabric weight 60 ± 20 g/m²
- Vinyl weight 290 ± 20 g/m²
- Method: ISO 2286-2
- Covering: acrylic paint specifically formulated with exclusive ink jet features

■ Details

- Roll wodth 1300 mm
- Roll Height 50 m
- Internal diameter 76 mm
- Package: box
- Light fastness 7 on 8 International Woolscale BS EN 20105 / ISO 105-B02
- Adhesive Strong wallcovering adhesive BK 10 (manual) or BK 23 (industrial) or similar PVA substitute
- Safety / Ecological the product is not dangerous. DIN 52900 or 91/55EEG, 2001/58/EC. To be man aged in controlled dumps or in solid waste incineratos
- Fire rating Euro class B1 - ABP nr B s1-d0 P-MPA-E-04-507

■ Specifications

Info about our product are based on our daylife experience. Buyers have to check the suitability of the product before using it. Buyers assume risk for any wrong use, operation or application. Information provided only describe the product and it does not concern any insurance. Specifications are subject to change without notice unless mistakes or omissions.

■ Warranty

Carta da Parati Artistica declares that the products comply with the Italian and EU regulations of the sector, applicable to the product category.

Carta da Parati Artistica declares that the products are made to perform the function of furnishing accessories and / or interior decoration.

Any complaints for product defects must be forwarded to the registered office of Carta da Parati Artistica, trademark of Tratto 16 Srls - Via Vittorio Veneto 16, 09016 Iglesias (SU), Italy within eight days and in any case before installation, under penalty of decline. The installation of the material implies the implicit waiver of the guarantees of the sale.

In case of discrepancy, the Customer must give Carta da Parati Artistica the possibility to verify the real presence of the defect also by sending pictures and / or samples of the complained product.










Any defect and / or deterioration and / or alteration of the product not attributable to the fact of Artistic Wallpaper is excluded from the guarantee, including:

- Chromatic alterations or differences in shades that fall within the normal tolerability of the product category.
- Defects deriving from installation without following the instructions provided by Artistic Wallpaper and / or the use of unsuitable or poor quality glue.
- Alterations or deteriorations resulting from the use of non-specific and / or corrosive cleaning products and / or in any case different from those indicated in the instructions provided by Wallpaper Artistic.
- Consequences on the product from use not in conformity with that for which it was made.
- Alterations or deteriorations caused by external factors and even accidental events, also due to the installation wall and / or the environment, such as humidity, scratches, tears, necklines, burns.





■ Certificates for use in interior decoration



	Certificate	Country	Logo	Description	UVgel 356 ink	UVgel 460 ink
	Greenguard Gold	Worldwide		VOC emissions for indoor spaces, Gold certifies for schools and hospitals	Certified	Expected Q4 2019
	EN15102	Europe		Mandatory for wallcovering sold in the EU. Tested o.a. on chemicals, robustness	Certified	Expected Q4 2019
	Emission dans l'air interieur	France		Mandatory emissions classification for wallcovering sold in France	Certified	Expected Q4 2019
	M1	Finland		Classification for emissions in building	Certified	Expected Q4 2019
	AgBB	Germany		VOC emissions standard for building materials	Certified	Expected Q4 2019
	ASTM F793	USA		Classifies wallcovering by use characteristics and serviceability	Type II certified	Expected Q4 2019

Canon

GEAR UP AND ACCELERATE COLORADO SALES ARENA

■ Installation

Detailed instructions on how to hang the wallcovering are inside the box. Instructions have an illustration diagram to understand the main steps.



It is highly suggested to rely on professional wall coverings workers for the application. Wall covering is provided with numbered rolls. A guide for the assembly is supplied.

WALL COVERING
Glass Fiber



■ Description

Glass Fiber wallcovering is a heavy covering ideal for décorating interior and exterior spaces in residential and commercial fields. Its surface could be emboss (as in the sample) or smooth. It can cover walls. Ceilings, showers, kitchens or saunas. It is necessary to apply it using only the indicated paste product.

■ Materials

The wallcover is made up of one layer in glass fiber. The wall covering has to be hang and resin has to be spread up following instructions. This wallcovering is durable and water resistant. Never soak it into water. It is the ideal solution for exterior long-last coverings as it can be pasted on many materials' surfaces.

Glass fiber cannot be removed without any residue, even using the best means because of its permanent adhesive.



■ Wall covering cleaning

Follow instructions contained in the resin section

■ Wall covering paste to use

To install glass fiber wall coverings, it is necessary to use the Ovalyt Metylan paste. This is not provided in the package because of its liquidity. You can buy it in a DIY store. This paste is ready to be pasted, no water is needed.

■ Use of glass fiber



Walls



Ceilings



Showers



Kitchens



Cold



Rain



Residential



Commercial

■ Technical characteristics

- 100% fiberglass material
- Total weight 185 ± 8%
- Loss on application 29% (minimum average value)
- Oekotex Standard 100 Certificate Product Class III (do not contain dangerous substances)
- Indoor air emission A + (very low)
- Fire resistance (EN 13501-1) Euroclass B, s1-d0 (A1, A2 board)
- Working conditions: dry room, storage temperature from -10 ° C to + 50 ° C.
If the product is not used within a week, it is not recommended to open the package
- Intended use of the product EN 15102: 2007 + A1: 2011 - Decorative and functional finishes of walls, walls and ceilings
- Test laboratory Nr. 0497 / CSI S.p.A.
- Formaldehyde release Pass test - EN15102: 2007 / A1: 2011
- Release of other substances dangerous, heavy metals and specific elements: Passed test - EN15102: 2007 / A1: 2011
- Sound absorption NPD - EN15102: 2007 / A1: 2011
- Thermal resistance NPD - EN15102: 2007 / A1: 2011

Info about our product are based on our daylife experience. Buyers have to check the suitability of the product before using it. Buyers assume risk for any wrong use, operation or application. Information provided only describe the product and it does not concern any insurance. Specifications are subject to change without notice unless mistakes or omissions.

■ Warranty

Carta da Parati Artistica declares that the products comply with the Italian and EU regulations of the sector, applicable to the product category.

Carta da Parati Artistica declares that the products are made to perform the function of furnishing accessories and / or interior decoration.

Any complaints for product defects must be forwarded to the registered office of Carta da Parati Artistica, trademark of Tratto 16 Srls - Via Vittorio Veneto 16, 09016 Iglesias (SU), Italy within eight days and in any case before installation, under penalty of decline. The installation of the material implies the implicit waiver of the guarantees of the sale.

In case of discrepancy, the Customer must give Carta da Parati Artistica the possibility to verify the real presence of the defect also by sending pictures and / or samples of the complained product.










Any defect and / or deterioration and / or alteration of the product not attributable to the fact of Artistic Wallpaper is excluded from the guarantee, including:

- Chromatic alterations or differences in shades that fall within the normal tolerability of the product category.
- Defects deriving from installation without following the instructions provided by Artistic Wallpaper and / or the use of unsuitable or poor quality glue.
- Alterations or deteriorations resulting from the use of non-specific and / or corrosive cleaning products and / or in any case different from those indicated in the instructions provided by Wallpaper Artistic.
- Consequences on the product from use not in conformity with that for which it was made.
- Alterations or deteriorations caused by external factors and even accidental events, also due to the installation wall and / or the environment, such as humidity, scratches, tears, necklines, burns.





■ Certificates for use in interior decoration



	Certificate	Country	Logo	Description	UVgel 356 ink	UVgel 460 ink
	Greenguard Gold	Worldwide		VOC emissions for indoor spaces, Gold certifies for schools and hospitals	Certified	Expected Q4 2019
	EN15102	Europe		Mandatory for wallcovering sold in the EU. Tested o.a. on chemicals, robustness	Certified	Expected Q4 2019
	Emission dans l'air interieur	France		Mandatory emissions classification for wallcovering sold in France	Certified	Expected Q4 2019
	M1	Finland		Classification for emissions in building	Certified	Expected Q4 2019
	AgBB	Germany		VOC emissions standard for building materials	Certified	Expected Q4 2019
	ASTM F793	USA		Classifies wallcovering by use characteristics and serviceability	Type II certified	Expected Q4 2019

Canon

GEAR UP AND ACCELERATE COLORADO SALES ARENA

■ Installation

Detailed instructions on how to hang the wallcovering are provided inside the box. Instructions have an illustration diagram to understand the main steps.



It is highly suggested to rely on professional wall coverings workers for the application. Wall covering is provided with numbered rolls. A guide for the assembly is supplied.

■ Resin

Transparent matt protective finish for decorative fiberglass coatings and wallpaper, even in humid rooms. It gives high resistance and abrasion and it is easy to clean, protecting the print.

The resin is supplied by us in 500ml bottles with detailed specifications on how to prepare the compound and on quantities needed.

Make sure that during the application phase the environment does not have any dust on the surface during the treatment of the resin and subsequent drying.

Apply the resin with doors and windows closed. Do not ventilate after application. Make sure that the air conditionings are off or are not activated with a timer during the entire period of application and subsequent drying.

Apply the resin 2/4 hours after applying the glue.

Duration of the mix: 90 minutes.

Ready for use (contact with water in the shower): 24 hours.

Mapecoat Decor Protection part B is harmful by inhalation, is irritating to the respiratory tract and can cause sensitization in contact with the skin in subjects sensitive to isocyanates.

During use, wear protective gloves and goggles and take the usual precautions for handling chemicals. In case of contact with eyes or skin, wash immediately and abundantly with water and consult your doctor. Use a suitable device respiratory protection.

Furthermore Mapecoat Decor Protection parts A and B are dangerous for the aquatic environment, it is recommended not to disperse the product in the environment.

For further and complete information regarding the safe use of the product, it is recommended to consult the last one version of the Safety Data Sheet.

USE RESTRICTED FOR PROFESSIONAL USERS.

The above information and requirements, while corresponding to our best experience, are from be considered, in any case, purely indicative and must be confirmed by exhaustive practical applications; therefore, before using the product, anyone who intends to use it is required to establish whether or not it is suitable for its intended use and, in any case, assumes all responsibility that may arise from its use.

• **Application procedure**

Preparation and application of the product.

Shake component A and pour it into a suitably prepared and clean tray.

Add component B, in the comp ratio. A: comp. B = 5: 1 (by weight) and mix thoroughly, until total homogenization. Apply with a short-haired roller or a crossed coat of Mapecoat Decor Protection.

• **Technical features**

Mapecoat Decor Protection is a 100% polyurethane, two-component, aliphatic water finish (non-yellowing)

- **Product properties**

- High wear resistance.
- Resists ultraviolet rays.
- Not yellowing.
- Seals the joints between one sheet and the other, subject to frequent washing or leaching.
- Resists various aggressive chemicals.
- Very easy to apply.
- Solvent free.
- Matte finish.
- Harmless to the health of the applicator and the end user.

In combination with Ultrabond Eco Decor Wet silylated polymer-based reactive adhesive, as well as products for the preparation of substrates and sealing that are most suitable for these types of applications, it constitutes a complete and safe system for the installation of decorative fiberglass and vinyl wallpaper with back in TNT in humid environments, even inside showers.

Particularly suitable also for facilitating the cleaning of fiberglass coverings and printed wallpaper and for the protection of the same from UV rays.

Always refer to the latest updated version of the technical data sheet on the website www.mapei.com

- **Cleaning**

The tools and residues of Mapecoat Decor Protection can be cleaned with water when the product is still fresh. Once hardened, it can only be removed mechanically.

- **Storage**

12 months in tightly closed original packaging. Store in a cool, dry place with a temperature ranging from 5 ° C to 35 ° C.

- **Risk data sheet**

Require the resin risk card before the application



Via Vittorio Veneto 16
Iglesias (CA) ITALY

www.cartadaparatiartistica.com
info@cartadaparatiartistica.com
+39 0781.35.00.59



Vers. 5.0 - 2022

I colori nel catalogo sono indicativi
© Tutti i diritti riservati

Made in Italy



Follow us



